

Method for coating synthetic articles and lacquer to be used for this method.

Patent Number: ☐ [EP0450625](#), [B1](#)
Publication date: 1991-10-09
Inventor(s): HOERTH FRANZ-JOSEF DR (DE); ROSE KLAUS DR (DE)
Applicant(s): FRAUNHOFER GES FORSCHUNG (DE)
Requested Patent: ☐ [DE4011045](#)
Application Number: EP19910105356 19910404
Priority Number(s): DE19904011045 19900405
IPC Classification: B05D3/00; C09D183/07; C09D183/08
EC Classification: [B05D7/02](#), [C08G77/58](#), [C09D183/08](#), [C09D183/14](#)
Equivalents: ☐ [WO9303088](#)
Cited Documents: [GB2137648](#); [EP0358011](#); [DE3100555](#); [EP0171493](#)

Abstract

The invention relates to a process for coating a plastic substrate in which a paint (varnish) prepared by hydrolytic condensation of one or more hydrolysable silicon compounds in which from 1 to 40 mol% of all Si bonded groups are non-hydrolysable groups containing an ethylenically unsaturated bond, and additionally non-hydrolysable groups containing a mercapto radical are present in such an amount that the ratio between ethylenically unsaturated bonds and mercapto radicals is from 25:1 to 1:1, is applied to the plastic substrate, the paint is cured by irradiation and optionally post-cured thermally, or the paint is cured thermally. The invention also relates to a paint for use in this process.

Data supplied from the esp@cenet database - 12